

Keeping Our Community Educated On the Quality of Our Drinking Water

The purpose of this report is to keep our Residents informed on the quality of their drinking water, and the monitoring requirements mandated by the Environmental Protection Agency (EPA). If you have any questions or concerns pertaining to this report, please call Jim Russo, Water Division Foreman, at (630) 620-2020.

The Village of Addison receives all of its water through the DuPage Water Commission (DWC), via the City of Chicago Jardine Water Filtration Plant. The Village of Addison has been supplying 100% Lake Michigan water since March of 1992. We receive and monitor incoming lake water from five different locations throughout the Village. In 2013 we purchased approximately 3.2 million gallons per day. The Village of Addison has two Water Pumping Stations, two elevated water tanks, a standpipe, and two ground storage tanks with a total storage capacity of 6,750,000 gallons.

To insure that the Village of Addison has the ability to supply water to our residents in an emergency, we also maintain six wells. In order to comply with all EPA requirements these wells are exercised and sampled monthly. This is done to insure that if needed, the well water would comply with all EPA requirements.

Lake Michigan is the sole source of drinking water for Addison, Chicago and many other suburban communities. The Environmental Protection Agency has found that the quality of Lake Michigan has improved dramatically over the past 30 years. Lake Michigan, by volume, is the second largest Great Lake and the only one located totally within the United States. It serves as a source of drinking water, as a place for swimming and fishing, as a scenic wonderland, and as a sink for municipal and industrial waste and runoff from the surrounding lands. All 63 miles of shoreline within Illinois are now considered to be in good condition. Since the quality of the raw water source is good, conventional treatment methods of disinfection. coagulation and sedimentation, and sand filtration are adequate for producing water that is free of harmful contaminants

In order to ensure that tap water is safe to drink, EPA prescribes regulations which limit the amount of certain contaminants in water provided by public water systems. FDA regulations establish limits for contaminants in bottled water which must provide the same protection for public health.

Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. More information about contaminants and potential health effects can be obtained by calling the EPA Safe Drinking Water Hotline at (800) 426-4791. Some people may be more vulnerable to contaminants in drinking water than the general population. Immuno-compromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly and infants can be particularly at risk from infections. These people should seek advice about drinking water from their health care providers. EPA/ CDC guidelines on appropriate means to lessen the risk of infection by Cryptosporidium and other microbial contaminants are available from the SAFE DRINKING WATER HOTLINE (1-800-426-4791).

The Village of Addison Water Division samples and monitors the water from the entire water distribution system every month as mandated by the Safe Drinking Water Act (SDWA). If the required samples are not submitted or if a sample would be found to be contaminated, this would be a violation of the SDWA and EPA regulations, and all Addison residents would have to be notified as soon as possible. Our Water Department collects 46 water samples every month to insure that your tap water is free from bacteria. These sampling points are distributed evenly throughout the Village. This year, as in past years, your drinking water has met all USEPA and State drinking water standards. The City of Chicago and the DuPage Water Commission also sample and test the water before it reaches the Village of Addison.

In addition to performing bacteriological testing, every

three years the village collects water samples at homes throughout the village to test for lead and copper contamination. Homes containing lead pipes, lead service lines or copper pipe soldered with lead based solder were chosen based on criteria set by the United States Environmental Protection Agency. If more than ten per cent of the collected samples exceed levels set by the USEPA, we would be notified by the IEPA of what actions we must take. The testing began in July 1992, and after two rounds of sampling, the IEPA reduced the number of samples and frequency. The Village of Addison was reduced from 60 tests to 30, due to the water being in compliance with lead and copper standards.

The Chicago Water Department monitors for contaminants which are proposed to be regulated or for which no standards currently exist but which could provide useful information in assessing the quality of the source water.

The sources of drinking water (both tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs and wells. As water travels over the surface of the land or through the ground, it dissolves naturally-occurring minerals and, in some cases, radioactive materials, and can pick up substances resulting from the presence of animals or from human activity. Contaminants that may be present in source water include:

A) Microbial contaminants, such as viruses and bacteria, which may come from sewage treatment plants, septic systems, agricultural livestock operations and wildlife.

B) Inorganic contaminants, such as salts and metals, which may be naturally occurring or result from urban storm water runoff, industrial or domestic wastewater discharges, oil and gas production, mining or farming.

C) Pesticides and herbicides, which may come from a variety of sources such as agriculture, urban storm water runoff, and residential uses.

D) Organic chemical contaminants, including synthetic and volatile organic chemicals, which are by-products of industrial processes and petroleum production, and can also come from gas stations, urban storm water runoff, and septic systems.

E) Radioactive contaminants, which can be naturally-occurring or be the result of oil and gas production and mining activities.

Explanations of the abbreviations and definitions you will need to understand the sampling data on the water quality sheet for 2013 are as follows: Maximum Contaminant Level Goal (MCLG)

-The level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs allow for a margin of safety.

Maximum Contaminant Level (MCL) - The highest level of a contaminant that is allowed in drinking water. MCLs are set as close to the MCLGs as feasible using the best available treatment technology.

Maximum Residual Disinfectant Level Goal (MRDLG) – The level of a drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contaminants.

Maximum Residual Disinfectant Level (MRDL) – The highest level of a drinking water disinfectant allowed in drinking water. There is convincing evidence that addition of a disinfectant is necessary for control of microbial contamination.

ppb micrograms per liter or parts per billion – or one ounce in 7,350,000 gallons of water.

- **nd** not detectable at testing limits
- **n**/**a** not applicable
- **ppm** parts per million, or milligrams per liter or one ounce in 7,350,000 gallons of water.
- Avg Regulatory compliance with some MCLs are based on running annual average of monthly samples.
- NTU Nephelometric Turbidity Unit, used to measure cloudiness in drinking water
- %<0.3 NTU Percent of samples less than or equal; to 0.3NTU
- **pCi/L** Picocuries per liter, used to measure radioactivity

Range of Detection- This column represents a range of individual sample results, from lowest to highest that were collected during the Consumer Confidence Report (CCR) calendar year.

Level Found- This column represents an average of sample data collected during the CCR calendar year. In some cases, it may represent a single sample if only one sample was collected.

Haloacetic acids - (HAA5) are disinfectant byproducts. The Village of Addison began monitoring for HAA5 in 2000. The City of Chicago started monitoring for HAA5 in July, 1998. All samples collected by the Village of Addison have been far below the levels set by the IEPA.

Lead and Copper

Definitions: Action Level (AL); The concentration of a contaminant which, if exceeded, triggers treatment or other requirements which a water system must follow. If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. We cannot control the variety of materials used in plumbing components When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the safe drinking water hotline or at http://www.epa.gov/safewater/lead.

Action level goal (ALG); The level of a contaminant in drinking water below which there is no known or expected risk to health. ALGs allow for a margin of safety.

Action Levels (AL) - The concentration of a contaminant which, if exceeded, triggers treatment or other requirements which a water system must

follow.

Trihalomethanes- are disinfectant by-products. The Village of Addison started sampling for Trihalomethanes in July 1987. The samples are collected quarterly.

Turbidity- is a measure of the cloudiness of the water. The City of Chicago monitors it because it is a good indicator of water quality and the effectiveness of their filtration system.

Fluoride- is added to the water supply to help promote strong teeth. The Illinois Department of Public Health recommends an optimal fluoride range of 0.9 mg/l to 1.2 mg/l.

Sodium- There is no state or federal MCL for sodium. Monitoring is required to provide information to consumers and health officials that are concerned about sodium intake due to dietary precautions. If the level is greater than 20 mg/l and you are on a sodium-restricted diet, you should consult a physician.

Cryptosporidium- Analyses' have been conducted monthly on the source water since April 1993. Cryptosporidium has not been detected in these samples. Cryptosporidium is a single-celled parasite, highly resistant to chlorine, which produces an illness characterized by vomiting, fever, diarrhea and fatigue when ingested. Treatment processes have been optimized to ensure that if there are cryptosporidium cysts in the source water, they will be removed during the treatment process. By maintaining a low turbidity and thereby removing the particles from the water, the threat of cryptosporidium organisms getting into the drinking water system is greatly reduced.

Chromium- Occurs naturally in the environment as chromite iron ore. It is rarely found naturally in water, yet it is widely distributed in soils and plants. Chromium in this form is an important contributor to human health. Chromium can also exist in a toxic state as Hexavalent Chromium, which is associated with industrial waste. Chromium is used in metal alloys including stainless steel, protective coatings on metal, magnetic tapes and pigments for paints, cement, paper and rubber. The USEPA determined that there is no evidence that the lifetime exposure to Chromium in drinking water can cause cancer. Hexavalent Chromium at acute levels can cause skin irritation or ulcerations; long-term exposure to Hexavalent Chromium can lead to liver and kidney damage as well as damage to nerve tissue. Hexavalant chromium has been successfully eliminated from entering the environment as a result of past and current national pollution discharge elimination system and industrial pollution discharge limits. The MCL for Chromium in drinking water is 100 ug/l.

UNREGULATED CONTAMINANTS:

A maximum contaminant level (MCL) for this contaminant has not been established by either the state or federal regulations, nor has mandatory health effect language. The purpose for monitoring this contaminant is to assist USEPA in determining the occurrence of unregulated contaminants in drinking water, and whether future regulation is warranted.

SOURCE WATER ASSESSMENT:

We want our valued customers to be informed about their water quality. If you would like to learn more, please feel welcome to attend any of our regularly scheduled meetings. The source water assessment for our supply has been completed by the Illinois EPA. To view a summary version of the completed Source Water Assessments, including: Importance of Source Water; Susceptibility to Contamination Determination; and documentation/recommendation of Source Water Protection Efforts, you may access the Illinois EPA website at http://www.epa.state.il.us/cgi-bin/wp/swapfact-sheets.pl.

The Illinois EPA considers all surface water sources of community water supply to be susceptible to potential pollution problems. The very nature of surface water allows contaminants to migrate into the intake with no protection only dilution. This is the reason for mandatory treatment for all surface water supplies in Illinois. Chicago's offshore intakes are located at a distance that shoreline impacts are not usually considered a factor on water quality. At certain times of the year, however, the potential for contamination exists due to wet-weather flows and river reversals. In addition, the placement of the crib structures may serve to attract waterfowl, gulls and terns that frequent the Great Lakes area, thereby concentrating fecal deposits at the intake and thus compromising the source water quality. Conversely, the shore intakes are highly susceptible to storm water runoff, marinas and shoreline point sources due to the influx of groundwater to the lake.

Throughout history there have been extraordinary steps taken to assure a safe source of drinking water in the Chicago land area. From the building of the offshore cribs and the introduction of interceptor sewers to the lock-and-dam system of Chicago's waterways and the city's Lakefront Zoning Ordinance. The city now looks to the recently created Department of the Water Management, Department of Environment and the MWRDGC (Metropolitan Water Reclamation District of Greater Chicago) to assure the safety of the city's water supply. Also, water supply officials from Chicago are active members of the West Shore Water Producers Association. Coordination of water quality situations (i.e., spills, tanker leaks, exotic species, etc) and general lake conditions are frequently discussed during the association's quarterly meetings. Also, Lake Michigan has a variety of organizations and associations that are currently working to either maintain or improve water quality. Finally, one of the best ways to ensure a safe source of drinking water is to develop a program designed to protect the source water against potential contamination on the local level. Since the predominant land use within Illinois' boundary of Lake Michigan watershed is urban, a majority of the watershed protection activities in this document are aimed at this purpose. Citizens should be aware that everyday activities in an urban setting might have a negative impact on their source water.

Efforts should be made to improve awareness of storm water drains and their direct link to the lake within the identified local source water area. A proven best management practice (BMP) for this purpose has been the identification and stenciling of storm water drains within a watershed. Stenciling along with an educational component is necessary to keep the lake a safe and reliable source of drinking water.

With the increased cost of water, water conservation has become a hot topic these days. You should be aware of water use in your home or business. One cause of higher than usual water bills, are leaking toilets. Water meters have a low flow indicator built into them to show very small water usage. This usage, can add up very rapidly to a high water bill. The low flow indicator is ether a red or white triangle located on the meter head. The slightest water usage will cause the triangle to turn. If you find the triangle turning and there is no faucet in your home running, you might have a leaking toilet.

The Village of Addison Water Division maintains over 170 miles of water main, 2300 fire hydrants with auxiliary valves, 1800 main water line valves and over 9000 water services. In 2013 the water division repaired 115 water main breaks as opposed to 85 in 2012. In 1989 we started an annual water main replacement program due to the volume and type of pipe deterioration we were experiencing back then and are still seeing today. All main installed after 1989 is sleeved in a plastic wrap to keep if from coming in contact with any corrosive soil. To date, there has never been a failure in the water main that has been replaced in this program.

Several years ago the Village of Addison passed an ordinance pertaining to Cross Connection and Backflow Protection, sighting the Illinois State Plumbing Code and the EPA (Environmental Protection Agency). We have been aggressively enforcing this ordinance (#0-04-120), and are making sure all backflow devices which encompass irrigation systems, fire sprinkler systems, and in some cases domestic water lines, are all in compliance. All backflow protection devices must be tested and certified on a yearly basis by a licensed plumber that is certified to test backflow devices. Failure to certify these devices will result in your water being turned off. A copy of the test data must also be sent to us for our records. The Village of Addison does not take part in any third party reporting program, endorse any plumbers or Plumbing Company or hire independent plumbers to perform Cross Control inspections. Also, Village of Addison no longer will send out reminder letters. It is your responsibility to have each device tested each year. The Village of Addison encourages you to seek out the best possible price for this certification and can provide you with a list of plumbers if you wish. This is an ongoing annual program. If residents and business owners are unsure if this pertains to them or have any questions please call Stewart McLeod, Water Operator, at (630) 620-2020.

The Village of Addison also has identified buildings with single detector check devices on their fire sprinkler systems. Single detector check devices or SDC are no longer acceptable backflow devices. The Illinois Environmental Protection Agency requires that all SDC valves on fire sprinkler systems be removed and upgraded to a Reduced Pressure Zone or RPZ. If your building contains a SDC you are required to contact the Community Development Department (630-543-4100) you will be required to obtain a permit for the upgrade. Your contractor will be required to show that the upgrade will not have an adverse effect on the original design of your sprinkler system.

If your home or business has an underground irrigation system, a RPZ must be installed to separate it from the Village Water Supply. No other valve is allowed for this application. If you have an irrigation system, but have chosen not to use it, the backflow device must be removed, separating the irrigation system from the Public Water Supply and both lines capped.

In your home or business, the Village of Addison is only responsible for the water meter and the threaded connections on either side of the meter. All other piping including the shut off valves in the building belongs to the home or Business owner.

The Chicago land area has just experienced one of the harshest winters on record. Along with a record snow fall exceeding 79 inches at O'Hare, making it the 3rd snowiest, it also was the coldest on record. With the cold setting in we also started experiencing frozen water services. Water services that never froze in the past were affected by the severe cold temperatures. The reason for this was the deep frost line in the ground. We experienced a 4 foot frost line. With that said, any water line that was in that frost line would freeze unless precautions were taken. The easiest way was to keep a low flow of water moving through the service line to prevent freezing.

VILLAGE OF ADDISON

No drinking water quality violations were recorded during 2013

Lead and Copper

	Date Sampled	MCLG	Action Level (AL)	90 th Percentile	# sites over AL	Units	Violation	Likely Source of Contamination
Copper	6/13/2011	1.3	1.3	0.21	0	ppm	No	Erosion of natural deposits; leaching from wood preservatives; corrosion of household plumbing systems
Lead	6/13/2011	0	15	2	0	ppb	No	Corrosion of household plumbing systems; Frosion of natural deposits

Regulated Contaminants

uranium

Disinfectants and Disinfection By-Products Collection Sampled		Sampled	Highest Level	Range of Detection		Units	MCLG		ľ	MCL Violat		olation	Likely Sources of Contaminants
Chlorine	12/31/2012		0.7	0.5 - 1		ppm	MRI	MRDLG=4		RDL=4	No		Water additive used to control microbes
Haloacetic Acids (HAA5)	2013		13	1	-21.2	ppb No th		goal for e total	60		No		By-product of drinking water chlorination.
Total Trihalomethanes (TTHM)	2013		32	14	- 50.51	ppb	No for th	goal he total		80		No	By-product of drinking water disinfection
Below are sample results collected from the Village of Addison Emergency Backup Wells and not Chicago Water													
Inorganic Contaminants	Collection Date	Highest Level Detected	Range Detect	e of tion	Units	MC	LG	MCI	L	Viola	tion	Likely Source of Contamination	
Arsenic	10/29/2012	2	2-2	2	ppb	0		10		No)	Erosion of natural deposits; Runoff from orchards; runoff from glass and electronics production waste.	
Barium	10/29/2012	0.037	0.037 - 0	0.037	ppm	2		2		No	,	Discharge of drilling wastes; Discharge from metal refineries; Erosion of natural deposits	
Iron	10/29/2012	3.8	3.8 - 3	3.8	ppm			1.0		Nc	,	This contaminant is not currently regulated the USEPA. However, the state regulate Erosion of natural deposits	
Manganese	10/29/2012	45	45 - 4	45	ppb	15	0	150		Nc	This contamin the USEPA Ero		EPA. However, the state regulated by EPA. However, the state regulates. Erosion of natural deposits
Sodium	10/29/2012	53	53 - 53		ppm				No			Erosion from naturally occurring deposits, Used in water softener regeneration	
Zinc	10/29/2012	0.024	0.024 - 0.024		ppm	5		5		No		This conta the USI Natural	aminant is not currently regulated by EPA. However, the state regulates. ly occurring; discharge from metal
Radioactive Contaminants	Collection Date	Highest Level Detected	Range of Detection		MCLG	МС	L Unit		S	Violation Likely		Likely	Source of Contamination
Combined Radium 226/228	8/24/2011	2.35	1.163 -	2.35	0	5		pCi/L		No		Decay	of natural and man-made deposits
Gross alpha excluding radon and	8/24/2011	1.72	1.3 – 1	.72	0	15	;	pCi/L		No	,	Decay	of natural and man-made deposits

MCL Statement: The Maximum contaminant level (MCL) for TTHM and HAAs is 80 ppb and 60 ppb respectively and is currently only applicable to surface water supplies that serve 10,000 or more people. These MCLs became effective 01/01/2004 for all groundwater supplies and surface supplies serving less than 10,000 people. Before 01/01/2004, surface water supplies serving less than 10,000 people, any size water supply that purchase from a surface water source, and groundwater supplies serving more than 10,000 people had to meet a state imposed TTHM MCL of 100 ppm. Some people who drink water containing Trihalomethanes in excess of the MCL over many years

CITY OF CHICAGO 2013 TEST RESULTS

No drinking water quality violations were recorded during 2013

Detected Contaminants

Contaminant (unit of measurement) Typical Source of Contaminant	MCLG	MCL	Highest Level Detected	RANGE OF DETECTION	COLLECTION DATE	
<u>Turbidity Data</u>						
TURBIDITY (NTU/Lowest Monthly %<0.3NTU) Soil runoff.	n/a	TT(95%<0.3NTU)	100%			
TURBIDITY (NTU/Highest Single Measurement) Soil runoff.	n/a	TT(1NTUmax)	0.18 NTU			
Inorganic Contaminants						
BARIUM (ppm) Discharge of drilling wastes; Discharge from metal refineries; Erosion of natural deposits	2	2	0.0205	0.0204 - 0.0205		
ARSENIC (ppb) Erosion of natural deposits; runoff from orchards; Runoff from glass and electronics production wastes	0	10	0.77	0.5190 - 0.767		
SELENIUM (ppb) Discharge from petroleum and metal refineries; Erosion of natural deposits; Discharge from mines.	50	50	50 2.48 ND - 2.48			
NITRATE (AS NITROGEN) (ppm) Runoff from fertilizer use; Leaching from septic tanks, sewage; Erosion of natural deposits	10	10	0.362	0.351 - 0.362		
TOTAL NITRATE & NITRITE (AS NITROGEN) (ppm) Runoff from fertilizer use; Leaching from septic tanks, sewage; Erosion of natural deposits	10	10	0.362	0.351 - 0.362		
Unregulated Contaminants						
SULFATE (ppm) Erosion of naturally occurring deposits.	n/a	n/a	11.9	ND – 11.9		
SODIUM (ppm) Erosion from naturally occurring deposits; Used in water softener.	n/a	n/a	7.84	7.42 - 7.84		
State Regulated Contaminants						
FLUORIDE (ppm) Water additive which promotes strong teeth	4	4	0.9	0.856 - 0.922		
Radioactive Contaminants						
Combined Radium 226/228 (pCi/L) Decay of natural and man-made deposits	0	5	1.38	1.300 - 1.380	03/17/2008	
GROSS ALPHA excluding radon and uranium (pCi/L) Decay of natural and man-made deposits	0	15	0.88	0.090 - 0.880	03/17/2008	

TOTAL ORGANIC CARBON

The percent of Total Organic Carbon (TOC) removal was measured each month and the system met all TOC removal requirements set by IEPA

NOTE: The Village of Addison data provided to us by the Illinois Environmental Protection Agency. The City of Chicago data provided to us by The City of Chicago.